Downlights

Alfa DL0007

Recessed spotlight




Recessed spotlight. 7 W. Three beam angles, 15° to 36°. 2700, 3000, 4000 K. IP54. 97 CRI.

- Ceiling cut-out Ø82 mm
- LED source: Citizen

Power **7 W**	Voltage **max 19 V**	Luminous flux **630 lm**
Colour temperature **2700 K, 3000 K, 4000 K**	CRI **97 CRI**	Beam angles **15°, 24°, 36°**
IP rating **IP54**	Certifications **CE**	Mounting **Recessed**
Finishes **White**		

Dimensions




Models


Code	Power	Voltage	Flux	CRI	Size	Cut-out	Beam	Notes
DL0007	7 W	max 19 V	630 lm	97 CRI	Ø92 x H38 mm	Ø82 mm	15° 24° 36°	350 mA

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL0007, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.


DL0007, 7 W, 15° beam






Luminous flux	630 lm
Efficacy	90 lm/W
Peak intensity	8,146 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø92 × 38 mm
Data	Calculated from catalogue data


DL0007, 7 W, 24° beam






Luminous flux	630 lm
Efficacy	90 lm/W
Peak intensity	3,202 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø92 × 38 mm
Data	Calculated from catalogue data

DL0007, 7 W, 36° beam





Luminous flux	630 lm
Efficacy	90 lm/W
Peak intensity	1,442 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø92 × 38 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.