Linear

Bet DL1651

Linear luminaire




Linear luminaire. 20 W. 90° beam. 2700, 3000, 4000 K. 97 CRI.

- Ceiling cut-out Ø276 mm
- LED source: Citizen

Power **20 W**	Voltage **max 32 V**	Luminous flux **1800 lm**
Colour temperature **2700 K, 3000 K, 4000 K**	CRI **97 CRI**	Beam angles **90°**
IP rating **IP20**	Certifications **CE**	Mounting **Recessed**
Finishes **Black**		

Dimensions




Models

Code	Version	Power	Voltage	Flux	CRI	Size	Cut-out	Beam	Notes
DL1651	Wall washer	20 W	max 32 V	1800 lm	97 CRI	L331 x W41 x H60 mm	Ø276 mm	90°	600 mA

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL1651, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

DL1651, 20 W, wall washer



Luminous flux	**1,800 lm**
Efficacy	**90 lm/W**
Peak intensity	**763 cd, 424 cd/klm**
Beam angle (50%)	**asymmetric**
Cut-off angle (2.5%)	**90°**
Flux 0–30° / 30–60° / 60–90°	**24.2 / 47.2 / 28.6 %**
Size	**331 × 41 × 60 mm**
Data	**Calculated from catalogue data**

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.