Outdoor

Bollard SL0083

Outdoor luminaire



Outdoor luminaire. 7 W. 2700, 3000, 4000 K. IP67. 97 CRI.

- LED source: Citizen

Power	Voltage	Luminous flux
7 W	24 V DC	560 lm
Colour temperature	**CRI**	**IP rating**
2700 K, 3000 K, 4000 K	97 CRI	IP67
Certifications	**Mounting**	**Finishes**
CE	Floor, Wall	Black


Models


Code	Power	Voltage	Flux	CRI	Size
SL0083	7 W	24 V DC	560 lm	97 CRI	Ø120 x H269 mm

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for SL0083, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

SL0083, 7 W, wide distribution





Luminous flux	**560 lm**
Efficacy	**80 lm/W**
Peak intensity	**178 cd, 318 cd/klm**
Beam angle (50%)	**120°**
Field angle (10%)	**168.5°**
Cut-off angle (2.5%)	**88.5°**
Flux 0–30° / 30–60° / 60–90°	**25 / 50 / 25 %**
Size	**Ø120 × 269 mm**
Data	**Calculated from catalogue data**

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.