Downlights

Dot DL0129

Recessed spotlight



Recessed spotlight. 3 W. Three beam angles, 24° to 60°. 2700, 3000, 4000 K. IP44. 97 CRI.

- LED source: Citizen

Power **3 W**	Voltage **max 10 V**	Luminous flux **280 lm**
Colour temperature **2700 K, 3000 K, 4000 K**	CRI **97 CRI**	Beam angles **24°, 36°, 60°**
IP rating **IP44**	Certifications **CE**	Mounting **Recessed, Surface**
Finishes **Black**		

Dimensions



Models

Code	Power	Voltage	Flux	CRI	Size	Beam	Notes
DL0129	3 W	max 10 V	280 lm	97 CRI	Ø60 × 18 mm	24° 36° 60°	350 mA

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL0129, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

DL0129, 3 W, 24° beam





Luminous flux	280 lm
Efficacy	93 lm/W
Peak intensity	1,423 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø60 × 18 mm
Data	Calculated from catalogue data

DL0129, 3 W, 36° beam





Luminous flux	280 lm
Efficacy	93 lm/W
Peak intensity	641 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø60 × 18 mm
Data	Calculated from catalogue data

DL0129, 3 W, 60° beam





Luminous flux	280 lm
Efficacy	93 lm/W
Peak intensity	241 cd, 860 cd/klm
Beam angle (50%)	60°
Field angle (10%)	109.4°
Cut-off angle (2.5%)	69°
Flux 0–30° / 30–60° / 60–90°	52.4 / 42.6 / 5 %
Size	Ø60 × 18 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.