Suspension

M1 Pendant

Pendant





Pendant. 10, 15 or 20 W. Three beam angles, 15° to 36°. 2700, 3000, 4000, 5000 K. 97 CRI.

- LED source: Citizen

Power **10 W, 15 W, 20 W**	Voltage **36 V**	Colour temperature **2700 K, 3000 K, 4000 K, 5000 K**
CRI **97 CRI**	Beam angles **15°, 24°, 36°**	IP rating **IP20**
Mounting **Suspended**	Control **On/Off, Triac**	Finishes **Black**

Dimensions








Models


Code	Power	Voltage	CRI	Size	Beam	Notes
PE-M1-1005	10 W	36 V	97 CRI	54 × 98 mm	15° 24° 36°	250 mA
PE-M1-1505	15 W	36 V	97 CRI	72 × 105 mm	15° 24° 36°	350 mA
PE-M1-2005	20 W	36 V	97 CRI	92 × 118 mm	15° 24° 36°	500 mA

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for PE-M1-2005, from the same data as the IES and LDT files on the product page. Estimated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.


PE-M1-2005, 20 W, 15° beam






Luminous flux	1,500 lm
Efficacy	75 lm/W
Peak intensity	19,394 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	118 × 92 mm
Data	Estimated from catalogue data


PE-M1-2005, 20 W, 24° beam






Luminous flux	1,500 lm
Efficacy	75 lm/W
Peak intensity	7,625 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	118 × 92 mm
Data	Estimated from catalogue data

PE-M1-2005, 20 W, 36° beam





Luminous flux	1,500 lm
Efficacy	75 lm/W
Peak intensity	3,434 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	118 × 92 mm
Data	Estimated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.