
Outdoor

Moon Outdoor DL1721

Outdoor luminaire




Outdoor luminaire. 5 W. Four beam angles, 15° to 60°. 2700, 3000, 4000 K. IP65. 97 CRI.

- Ceiling cut-out Ø35 mm
- LED source: Citizen

Power **5 W**	Voltage **max 19 V**	Luminous flux **450 lm**
Colour temperature **2700 K, 3000 K, 4000 K**	CRI **97 CRI**	Beam angles **15°, 24°, 36°, 60°**
IP rating **IP65**	Certifications **CE**	Mounting **Recessed, Wall**
Finishes **White**		

Dimensions




Models


Code	Power	Voltage	Flux	CRI	Size	Cut-out	Beam	Notes
DL1721	5 W	max 19 V	450 lm	97 CRI	Ø40 x H63 mm	Ø35 mm	15° 24° 36° 60°	250 mA

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL1721, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.


DL1721, 5 W, 15° beam






Luminous flux	450 lm
Efficacy	90 lm/W
Peak intensity	5,818 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø40 × 63 mm
Data	Calculated from catalogue data


DL1721, 5 W, 24° beam






Luminous flux	450 lm
Efficacy	90 lm/W
Peak intensity	2,287 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø40 × 63 mm
Data	Calculated from catalogue data


DL1721, 5 W, 36° beam






Luminous flux	450 lm
Efficacy	90 lm/W
Peak intensity	1,030 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø40 × 63 mm
Data	Calculated from catalogue data

DL1721, 5 W, 60° beam





Luminous flux	450 lm
Efficacy	90 lm/W
Peak intensity	387 cd, 860 cd/klm
Beam angle (50%)	60°
Field angle (10%)	109.4°
Cut-off angle (2.5%)	69°
Flux 0–30° / 30–60° / 60–90°	52.4 / 42.6 / 5 %
Size	Ø40 × 63 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.