Moon system

Moon Series D M-D133A

Moon spotlight




Spotlight for the Moon magnetic track. 8 W. 120° beam. 2700, 3000, 4000 K. 97 CRI.

- LED source: Citizen

Power	Voltage	Colour temperature
8 W	48 V DC	2700 K, 3000 K, 4000 K
CRI	**Beam angles**	**IP rating**
97 CRI	120°	IP20
Mounting	**Control**	**Finishes**
Suspended, Magnetic track	On/Off, Triac	Black

Dimensions




Models


Code	Version	Power	Voltage	CRI	Size	Beam	Notes
M-D133A				97 CRI		120°	
M-D133A	Ø133 mm	8 W	48 V DC	97 CRI	Ø133 × 82 mm; adapter 152 mm	120°	LED 36 V, 200 mA

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for M-D133A, from the same data as the IES and LDT files on the product page. Estimated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

M-D133A, 8 W, 120° beam





Luminous flux	480 lm
Efficacy	60 lm/W
Peak intensity	143 cd, 298 cd/klm
Beam angle (50%)	120°
Cut-off angle (2.5%)	90°
Flux 0–30° / 30–60° / 60–90°	23 / 45.1 / 31.8 %
Size	Ø133 × 82 mm
Data	Estimated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.