Wall Lamps

Oval Indoor WL0114

Wall light




Wall light. 11 W. 2700, 3000, 4000 K. 97 CRI.

- LED source: Citizen

Power	Voltage	Luminous flux
11 W	230 V AC	630 lm
Colour temperature	**CRI**	**IP rating**
2700 K, 3000 K, 4000 K	97 CRI	IP20
Certifications	**Mounting**	**Finishes**
CE	Surface, Wall	Black

Dimensions




Models


Code	Power	Voltage	Flux	CRI	Size
WL0114	11 W	230 V AC	630 lm	97 CRI	Ø80 × 34 mm back plate; 108 × 135 mm

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for WL0114, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

WL0114, 11 W, wide distribution





Luminous flux	630 lm
Efficacy	57 lm/W
Peak intensity	201 cd, 318 cd/klm
Beam angle (50%)	120°
Field angle (10%)	168.5°
Cut-off angle (2.5%)	88.5°
Flux 0–30° / 30–60° / 60–90°	25 / 50 / 25 %
Size	Ø80 × 34 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.