
Wall Lamps

Oval Outdoor WL0085

Wall light



Wall light. 8 W. 2700, 3000, 4000 K. IP65. 97 CRI.

- LED source: Citizen

Power	Voltage	Luminous flux
8 W	230 V AC	400 lm
Colour temperature	**CRI**	**IP rating**
2700 K, 3000 K, 4000 K	97 CRI	IP65
Certifications	**Mounting**	**Finishes**
CE	Surface, Wall	Black


Models


Code	Power	Voltage	Flux	CRI	Size
WL0085	8 W	230 V AC	400 lm	97 CRI	80 × 80 × 160 mm

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for WL0085, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

WL0085, 8 W, wide distribution





Luminous flux	400 lm
Efficacy	50 lm/W
Peak intensity	127 cd, 318 cd/klm
Beam angle (50%)	120°
Field angle (10%)	168.5°
Cut-off angle (2.5%)	88.5°
Flux 0–30° / 30–60° / 60–90°	25 / 50 / 25 %
Size	80 × 80 × 160 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.