Downlights

Robo DL1807

Recessed spotlight



Recessed spotlight. 6 W. Four beam angles, 15° to 60°. 2700, 3000, 4000 K. 97 CRI.

- Ceiling cut-out Ø118 mm
- LED source: Citizen

Power	Voltage	Luminous flux
6 W	max 9 V	3 × 140 lm
Colour temperature	**CRI**	**Beam angles**
2700 K, 3000 K, 4000 K	97 CRI	15°, 24°, 36°, 60°
IP rating	**Certifications**	**Mounting**
IP20	CE	Recessed
Finishes		
White		

Dimensions



Models

Code	Power	Voltage	Flux	CRI	Cut-out	Beam	Notes
DL1807	6 W	max 9 V	3 × 140 lm	97 CRI	Ø118 mm	15° 24° 36° 60°	700 mA

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL1807, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

DL1807, 6 W, 15° beam





Luminous flux	420 lm
Efficacy	70 lm/W
Peak intensity	5,430 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Data	Calculated from catalogue data

DL1807, 6 W, 24° beam





Luminous flux	420 lm
Efficacy	70 lm/W
Peak intensity	2,135 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Data	Calculated from catalogue data

DL1807, 6 W, 36° beam





Luminous flux	420 lm
Efficacy	70 lm/W
Peak intensity	961 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Data	Calculated from catalogue data

DL1807, 6 W, 60° beam





Luminous flux	420 lm
Efficacy	70 lm/W
Peak intensity	361 cd, 860 cd/klm
Beam angle (50%)	60°
Field angle (10%)	109.4°
Cut-off angle (2.5%)	69°
Flux 0–30° / 30–60° / 60–90°	52.4 / 42.6 / 5 %
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.