Downlights

Robo Zoom DL1345

Recessed spotlight




Recessed spotlight. 26 W. 2700, 3000, 4000 K. 97 CRI.

- Ceiling cut-out Ø150 mm
- LED source: Citizen

Power	Voltage	Luminous flux
26 W	2 × max 37 V	2 × 1180 lm
Colour temperature	**CRI**	**IP rating**
2700 K, 3000 K, 4000 K	97 CRI	IP20
Certifications	**Mounting**	**Finishes**
CE	Recessed	White

Dimensions




Models


Code	Version	Power	Voltage	Flux	CRI	Size	Cut-out	Notes
DL1345	2 heads, 15–60°	26 W	2 × max 37 V	2 × 1180 lm	97 CRI	158 × 86 x H94 mm, Ø50 head	Ø150 mm	350 mA; Power per head

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL1345, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

DL1345, 26 W, wide distribution





Luminous flux	2,360 lm
Efficacy	91 lm/W
Peak intensity	751 cd, 318 cd/klm
Beam angle (50%)	120°
Field angle (10%)	168.5°
Cut-off angle (2.5%)	88.5°
Flux 0–30° / 30–60° / 60–90°	25 / 50 / 25 %
Size	Ø50 × 94 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.