Downlights

SR-TL03A-1001

Recessed spotlight



Recessed spotlight. 10 or 15 W. Beam angles 15° to 60°, by model. 2700, 3000, 4000, 6000 K. IP20/65. 97 CRI.

- Ceiling cut-out Ø60 / Ø70 mm
- LED source: Citizen

Power **10 W, 15 W**	Voltage **36 V**	Colour temperature **2700 K, 3000 K, 4000 K, 6000 K**
CRI **97 CRI**	Beam angles **15°, 24°, 36°, 50°, 60°**	IP rating **IP20/65**
Mounting **Recessed**	Control **On/Off, Triac**	Finishes **Black**


Models


Code	Version	Power	Voltage	CRI	Size	Cut-out	Beam	Notes
SR-TL03A-1001	Trimless	10 W	36 V	97 CRI	Ø93 × 66 mm	Ø60 mm	15° 24° 36° 50°	250 mA
SR-TL03B-1501	Trimless	15 W	36 V	97 CRI	Ø104 × 77 mm	Ø70 mm	24° 36° 60°	350 mA
SR-TL03A-1501	Trimless	15 W	36 V	97 CRI	Ø104 × 77 mm	Ø70 mm	15° 24° 36° 50°	350 mA

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for SR-TL03B-1501, from the same data as the IES and LDT files on the product page. Estimated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.


SR-TL03B-1501, 15 W, 24° beam






Luminous flux	1,125 lm
Efficacy	75 lm/W
Peak intensity	5,719 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø104 × 77 mm
Data	Estimated from catalogue data


SR-TL03B-1501, 15 W, 36° beam






Luminous flux	1,125 lm
Efficacy	75 lm/W
Peak intensity	2,575 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø104 × 77 mm
Data	Estimated from catalogue data

SR-TL03B-1501, 15 W, 60° beam





Luminous flux	1,125 lm
Efficacy	75 lm/W
Peak intensity	968 cd, 860 cd/klm
Beam angle (50%)	60°
Field angle (10%)	109.4°
Cut-off angle (2.5%)	69°
Flux 0–30° / 30–60° / 60–90°	52.4 / 42.6 / 5 %
Size	Ø104 × 77 mm
Data	Estimated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.