
Ceiling

# SU-M6-1002

Surface luminaire




Surface luminaire. 10 W. Four beam angles, 15° to 50°. 2700, 3000, 4000, 5000 K. 97 CRI.

- LED source: Citizen

| | | |
|---|---|---|
| Power<br>**10 W** | Voltage<br>**36 V** | Colour temperature<br>**2700 K, 3000 K, 4000 K, 5000 K** |
| CRI<br>**97 CRI** | Beam angles<br>**15°, 24°, 36°, 50°** | IP rating<br>**IP20** |
| Mounting<br>**Surface** | Control<br>**On/Off, Triac** | Finishes<br>**Black** |

## Dimensions





## Models


| Code | Power | Voltage | CRI | Size | Beam | Notes |
|---|---|---|---|---|---|---|
| SU-M6-1002 | 10 W | 36 V | 97 CRI | 150 × 110 × 30 mm | 15° 24° 36° 50° | 250 mA |

# Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for SU-M6-1002, from the same data as the IES and LDT files on the product page. Estimated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.


## SU-M6-1002, 10 W, 15° beam





| | |
|---|---|
| Luminous flux | 750 lm |
| Efficacy | 75 lm/W |
| Peak intensity | 9,697 cd, 12,930 cd/klm |
| Beam angle (50%) | 15° |
| Field angle (10%) | 27.3° |
| Cut-off angle (2.5%) | 17° |
| Flux 0–30° / 30–60° / 60–90° | 100 / 0 / 0 % |
| Size | 150 × 110 × 30 mm |
| Data | Estimated from catalogue data |


## SU-M6-1002, 10 W, 24° beam





| | |
|---|---|
| Luminous flux | 750 lm |
| Efficacy | 75 lm/W |
| Peak intensity | 3,812 cd, 5,083 cd/klm |
| Beam angle (50%) | 24° |
| Field angle (10%) | 43.7° |
| Cut-off angle (2.5%) | 27.5° |
| Flux 0–30° / 30–60° / 60–90° | 98.7 / 1.3 / 0 % |
| Size | 150 × 110 × 30 mm |
| Data | Estimated from catalogue data |


## SU-M6-1002, 10 W, 36° beam





| | |
|---|---|
| Luminous flux | 750 lm |
| Efficacy | 75 lm/W |
| Peak intensity | 1,717 cd, 2,289 cd/klm |
| Beam angle (50%) | 36° |
| Field angle (10%) | 65.6° |
| Cut-off angle (2.5%) | 41.5° |
| Flux 0–30° / 30–60° / 60–90° | 86.1 / 13.9 / 0 % |
| Size | 150 × 110 × 30 mm |
| Data | Estimated from catalogue data |

## SU-M6-1002, 10 W, 50° beam




| | |
|---|---|
| Luminous flux | **750 lm** |
| Efficacy | **75 lm/W** |
| Peak intensity | **910 cd, 1,213 cd/klm** |
| Beam angle (50%) | **50°** |
| Field angle (10%) | **91.1°** |
| Cut-off angle (2.5%) | **57.5°** |
| Flux 0–30° / 30–60° / 60–90° | **64.8 / 33.6 / 1.5 %** |
| Size | **150 × 110 × 30 mm** |
| Data | **Estimated from catalogue data** |

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.