Track Spotlights

Tour Forty8 TR0260

Track spotlight



Track spotlight. 9 W. Four beam angles, 15° to 55°. 2700, 3000, 4000 K. 97 CRI.

- LED source: Citizen

Power 9 W	Voltage 48 V DC	Luminous flux 720 lm
Colour temperature 2700 K, 3000 K, 4000 K	CRI 97 CRI	Beam angles 15°, 24°, 36°, 55°
IP rating IP20	Certifications CE	Mounting Magnetic track
Finishes Black		


Models

Code	Power	Voltage	Flux	CRI	Size	Beam
TR0260	9 W	48 V DC	720 lm	97 CRI	Ø45 × 82 mm	15° 24° 36° 55°

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for TR0260, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

TR0260, 9 W, 15° beam




Luminous flux	720 lm
Efficacy	80 lm/W
Peak intensity	9,309 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø45 × 82 mm
Data	Calculated from catalogue data

TR0260, 9 W, 24° beam




Luminous flux	720 lm
Efficacy	80 lm/W
Peak intensity	3,660 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø45 × 82 mm
Data	Calculated from catalogue data


TR0260, 9 W, 36° beam



Luminous flux	720 lm
Efficacy	80 lm/W
Peak intensity	1,648 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø45 × 82 mm
Data	Calculated from catalogue data

TR0260, 9 W, 55° beam





Luminous flux	720 lm
Efficacy	80 lm/W
Peak intensity	729 cd, 1,012 cd/klm
Beam angle (50%)	55°
Field angle (10%)	100.2°
Cut-off angle (2.5%)	63°
Flux 0–30° / 30–60° / 60–90°	58.2 / 38.8 / 3 %
Size	Ø45 × 82 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.