
FLEXA
LIGHTING

24VDC DEEP TRACK

Linear system

IP20 made in Italy



24VDC track for surface or suspended installation. The system includes a wide range of accessories that allow the coupling of several electrified tracks.


Binario 24VDC per installazione superficiale o sospesa. Il sistema comprende un'ampia serie di accessori che permettono l'accoppiamento di più binari elettrificati.

Rail 24VDC pour installation en surface ou suspendue. Le système comprend une large gamme d'accessoires qui permettent le couplage de plusieurs voies électrifiées.

24VDC Stromschiene zur oberflächlichen oder hängende Installation. Das System umfasst eine ganze Reihe von Zubehörteilen, die die Kopplung mehrerer elektrifizierter Gleise ermöglichen.

Carril 24VDC para instalación en superficie o suspendida. El sistema incluye una amplia gama de accesorios que permiten el acoplamiento de varias vías electrificadas.

Dimensions




Code construction

24TKD X X


1 1 mt **2** 2 mt **3** 3 mt

1 White **5** Black


Load schemes




Accessories




24TKD011 White
24TKD015 Black
Live-end




24TKD021 White
24TKD025 Black
Electrical straight joint




24TKD091 White
24TKD095 Black
Mechanical straight joint




24TKD031 White
24TKD035 Black
Electrical L joint




24TKD041 White
24TKD045 Black
Mechanical L joint




24TKD051 White
24TKD055 Black
Dead end



24TKD061 White
24TKD065 Black
3000mm track cover



24TKD-K01
Suspension kit with 2000mm steel wire and automatic locking device



24TKD10
Reinforcing bracket for linear junction

Drivers 24VDC

on/off

AL2012 25W IP20 60 mm
AL2031 70W IP20 70 mm
AL2040 150W IP20 80 mm

dimmable

AL5012 24W IP20 DALI 2 PUSH 0/1..10V 45 mm
AL5241 100W IP20 DALI 2 PUSH 70 mm


dimming module

AL7035 IP20 DALI 2 PUSH 0/1..10V 44 mm


Note - Nota
Dimming module AL7035 to be used in combination with a 24VDC on/off power supply.
Modulo di dimmerazione AL7035 da utilizzare in combinazione con un alimentatore 24VDC on/off.

FLEXA
LIGHTING


Lighting modules




MINIJOS T2
2W - 24VDC




MINIJOS T6
6W - 24VDC




MINIJOS T10
10W - 24VDC




JOS T2
2W - 24VDC




JOS T6
6W - 24VDC




JOS T10
10W - 24VDC




LAD T6
6W - 24VDC




LAD T10
10W - 24VDC




LAD T10 WALL WASHER
10W - 24VDC




MICK T6
6W - 24VDC




MICK T10
10W - 24VDC




ESME PRECISION T2
2W - 24VDC




ESME PRECISION T4
4W - 24VDC




ESME PRECISION T10
10W - 24VDC



ESME PRECISION T20
20W - 24VDC



ESME PERFORMANCE T10
10W - 24VDC



ESME PERFORMANCE T20
20W - 24VDC



JOS T2P
2W - 24VDC



JOS T6P
6W - 24VDC



JOS T10P
10W - 24VDC



GAGARIN T2
2W - 24VDC



GAGARIN T6
6W - 24VDC



GAGARIN T10
10W - 24VDC