
FLEXA
LIGHTING

BIRDIE

Steplight

design Jude Allen

40mm IP40 made in Italy



The Birdie range offers asymmetrically emitting luminaires that combine high performance with a minimalist geometry and small dimensions, providing a stylish and effective design detail.

La gamma Birdie propone apparecchi ad emissione asimmetrica che uniscono alte prestazioni ad una geometria minimale ed a dimensioni ridotte, offrendo un elemento compositivo discreto ed efficace.

La gamme Birdie propose des luminaires à émission asymétrique qui combinent de hautes performances avec une géométrie minimaliste et des dimensions réduites, offrant un élément de composition simple et performant.

Die Birdie-Reihe bietet asymmetrisch abstrahlende Leuchten, die hohe Leistung mit einer minimalistischen Geometrie und geringen Abmessungen kombinieren und so ein diskretes und wirkungsvolles Gestaltungselement darstellen.

La gama Birdie ofrece luminarias de emisión asimétrica que combinan un alto rendimiento con una geometría minimalista y unas dimensiones reducidas, proporcionando un elemento compositivo elegante y eficiente.

Supply current
350-500mA (V_f 2,9V)


Power
1-2W

Serie wiring


CRI
85 (2200K-4200K)
90 (2700K-3000K)

2-Step MacAdam

Dimensions



Photometric diagrams



CCT/CRI/Flux

	350mA	500mA
2200K	**106 lm**	**152 lm**
2700K	**116 lm**	**166 lm**
3000K	**124 lm**	**177 lm**
4200K	**137 lm**	**204 lm**

Code construction


BDE X X

5	0	1	2
2200K	2700K	3000K	4200K

1	2	5	6
White	Grey	Black	Bronze

Accessories

CSDS05
Recessing box



Drivers 350mA

on/off
AL1034 (1..11) IP20 30 mm
AL1035 (1..11) IP20 40 mm
AL1037 (1..16) IP20 S.P. 55 mm

dimmable
AL4000 (1..12) IP20 PUSH 0/1..10V 72 mm
ALMINI35 (1..12) IP20 DALI 2 PUSH 30 mm
AL4051 (1..14) IP20 DALI 2 PUSH 72 mm
AL4053 (1..14) IP20 PUSH IGBT-TRIAC 56 mm

Drivers 500mA

on/off
AL1074 (1..7) IP20 30 mm
AL1077 (1..6) IP20 40 mm
AL1084 (1..11) IP20 S.P. 55 mm

dimmable
AL4010 (1..12) IP20 PUSH 0/1..10V 72 mm
ALMINI50 (1..8) IP20 DALI 2 PUSH 30 mm
AL4151 (1..14) IP20 DALI 2 PUSH 72 mm
AL4153 (1..14) IP20 PUSH IGBT-TRIAC 56 mm