FLEXA
LIGHTING

DAGO 6

Steplight

40x60mm

IP40 made in Italy

design Roberto Mantovani



The Dago range proposes asymmetrical emission fixtures that combine high performance with compactness in a minimal and discrete compositional element able to generate effective and fascinating lighting effects.

La gamma Dago propone apparecchi ad emissione asimmetrica che uniscono alte prestazioni ad una dimensione ridotta, offrendosi come elemento compositivo minimale e discreto, in grado di generare efficaci ed interessanti effetti luminosi.

La gamme Dago propose des appareils à émission asymétrique qui unissent des prestations élevées à une dimension réduite, ce qui fait d'elle un élément de composition minimal et discret, capable de générer des effets lumineux efficaces et intéressants.

Die Produktreihe Dago bietet Geräte mit asymmetrischer Strahlung, die beste Leistung mit kleiner Größe kombinieren, und bietet sich als ein minimalistisches und diskretes kompositorisches Element an, das wirksame und interessante Lichteffekte erzeugen kann.

La gama Dago propone aparatos de emisión asimétrica que combinan altas prestaciones con un tamaño reducido, y se presenta como un componente minimalista y discreto, capaz de crear efectos luminosos eficaces e interesantes.

Supply current
350-500mA (V_f 8,7V)


Power
3-6W

Serie wiring


CRI
85 (2200K-4200K-6000K)
90 (2700K-3000K)

2-Step MacAdam

Dimensions



Photometric diagrams



CCT/CRI/Flux

	350mA	500mA
2200K	**243 lm**	**350 lm**
2700K	**267 lm**	**384 lm**
3000K	**279 lm**	**400 lm**
4200K	**309 lm**	**462 lm**
6000K	**342 lm**	**495 lm**

Code construction


DG6 X 2 X

5	0	1	2	3	6	7	8
2200K	2700K	3000K	4200K	6000K	Blue	Green	Red

1	2	5	6
White	Grey	Black	Bronze

Accessories

CS1007
Recessing box



Drivers 350mA

on/off
AL1034 (1..3) IP20 30 mm
AL1035 (1..3) IP20 40 mm
AL1037 (1..5) IP20 S.P. 55 mm

dimmable
AL4000 (1..4) IP20 PUSH 0/1..10V 72 mm
ALMINI35 (1..4) IP20 DALI 2 PUSH 30 mm
AL4051 (1..4) IP20 DALI 2 PUSH 72 mm
AL4053 (1..4) IP20 PUSH IGBT-TRIAC 56 mm

Drivers 500mA

on/off
AL1074 (1..2) IP20 30 mm
AL1077 (1..2) IP20 40 mm
AL1084 (1..3) IP20 S.P. 55 mm

dimmable
AL4010 (1..4) IP20 PUSH 0/1..10V 72 mm
ALMINI50 (1..2) IP20 DALI 2 PUSH 30 mm
AL4151 (1..4) IP20 DALI 2 PUSH 72 mm
AL4153 (1..4) IP20 PUSH IGBT-TRIAC 56 mm