FLEXA
LIGHTING

GLASS 724

Uplight

IP67 made in Italy

design Roberto Mantovani



A walkable IP67 for ground recessing of the highest build quality and with a glass front. Extremely small dimensions combine with elevated luminous fluxes. With a body in thick anodised aluminium, it has tempered extra-clear glass, an ATEX cable gland and neoprene cable. Can be fitted with an anti-glare filter for maximum visual comfort.

Incassi a terra IP67 calpestabili di altissima qualità costruttiva, con frontale in vetro. Dimensioni estremamente contenute ed elevati flussi luminosi. Corpo in alluminio anodizzato a spessore, vetro extrachiaro temprato, pressacavo ATEX, cavo in neoprene. Equipaggiabili con filtro antiabbagliamento per il massimo comfort visivo.

Spots à encastrer au sol IP67 de très haute qualité de construction, avec façade en verre. Dimensions extrêmement limitées et à flux lumineux élevés. Corps en aluminium anodisé épais, verre extra-clair trempé, presse-étoupe ATEX, câble en néoprène Peut être équipé de filtre anti-éblouissement pour le plus grand confort visuel.

IP67 begehbare Bodeneinbauleuchten von sehr hoher Bauqualität, mit Glasfront. Extrem kleine Abmessungen und hohe Lichtströme. Dickes, eloxiertes Aluminiumgehäuse, gehärtetes, extraklares Glas, ATEX-Kabelverschraubung, Neoprenkabel. Kann mit Blendschutzfilter für maximalen Sehkomfort ausgestattet werden.

Luminarias empotrables de suelo IP67 transitables de muy alta calidad de fabricación, con frente de vidrio. Dimensiones extremadamente reducidas y elevados flujos luminosos. Cuerpo grueso de aluminio anodizado, cristal extraclaro templado, prensaestopas ATEX, cable de neopreno. Se puede equipar con un filtro antideslumbrante para un máximo confort visual.

Supply current
24VDC


Power
7W

Parallel wiring

CRI
85 (2200K)
93 (2700K-3000K-4000K)


2-Step MacAdam

Dimensions




Photometric diagrams


F971 - 36°



F972 - 46°



F973 - 60°



CCT/CRI/Flux

2200K — **570 lm**
2700K — **590 lm**
3000K — **650 lm**
4000K — **670 lm**

Code construction

GS7 X X


	S	M	W
	36°	46°	60°

18	29	39	49
2200K	2700K	3000K	4000K

Note
Made-to-measure cable available on request.

Accessories

CSGS07
Recessing box



Note
Recessing box needed for installation.

LGS701
Low luminance louver

HMGS701
Halfmoon glare shield (for round versions only)

Note
The filter and the half-moon glare shield must be ordered together with the lighting fixture.

Drivers 24VDC

on/off

AL2124 (1) IP20 28 mm
AL2012 (1..3) IP20 60 mm
AL2031 (1..10) IP20 70 mm
AL2040 (1..21) IP20 80 mm
AL9222 (1..5) IP67 44 mm
AL9231 (1..10) IP67 85 mm
AL9240 (1..21) IP67 85 mm

dimmable

AL5012 (1..3) IP20 DALI 2 PUSH 0/1..10V 45 mm
AL5241 (3..14) IP20 DALI 2 PUSH 70 mm
AL8012 (1..3) IP67 DALI 2 48 mm

dimming module

AL7035 IP20 DALI 2 PUSH 0/1..10V 44 mm

Note
Dimming module AL7035 to be used in combination with a 24VDC on/off power supply.