FLEXA
LIGHTING

KING

Pathlight

INOX IK10 IK09 IP67 made in Italy

design Roberti Mantovani



The King range offers IP67-rated, recessed ground fixtures for grazing lighting with 360° light emission. Utmost attention to detail and the highest optical and mechanical qualities make this a high-end product.

La gamma King offre incassi a terra IP67 per luce in radenza con emissione luminosa a 360°. Cura del dettaglio e qualità ottica e meccanica ne fanno un prodotto di alta gamma.

La gamme King propose des encastrables au sol IP67 pour lumière à ras avec émission lumineuse à 360°. Soin du détail et qualité optique et mécanique en font un produit de haute gamme.

Die Produktreihe King bietet Einbauten am Boden mit Schutzklasse IP67 für Streiflicht mit Lichtstrahlen von 360°. Liebe zum Detail und optische und mechanische Qualität machen es zu einem hochwertige Produkt.

La gama King ofrece empotrados de suelo IP67 para emitir luz al ras del suelo con emisión luminosa a 360°. Atención por los detalles y calidad óptica y mecánica crean un producto de alta gama.

Supply current
350-500mA (V_f 8,7V)


Power
3-6W

Series wiring

CRI
85 (2200K-4200K-6000K)
90 (2700K-3000K)

2-Step MacAdam

Dimensions



CCT/CRI/Flux

	350mA	500mA
2200K	**243 lm**	**350 lm**
2700K	**267 lm**	**384 lm**
3000K	**279 lm**	**400 lm**
4200K	**309 lm**	**462 lm**
6000K	**342 lm**	**495 lm**

Code construction

KG0 X X


5	0	1	2	3	6	7	8
2200K	2700K	3000K	4200K	6000K	Blue	Green	Red

G	A	N	V	K	Z
Grey	Anthracite	Black	Olive green	COR-TEN	INOX Steel AISI 316L

Note
Made-to-measure cable available on request.

Accessories

CSDS10
Recessing box



Drivers 350mA

on/off
AL1034 (1..3) IP20 30 mm
AL1035 (1..3) IP20 40 mm
AL1037 (1..5) IP20 S.P. 55 mm
AL9011 (1..4) IP67 44 mm

dimmable
AL4000 (1..4) IP20 PUSH 0/1..10V 72 mm
ALMINI35 (1..4) IP20 DALI 2 PUSH 30 mm
AL4051 (1..4) IP20 DALI 2 PUSH 72 mm
AL4053 (1..4) IP20 PUSH IGBT-TRIAC 56 mm
AL6035 (1..3) IP67 DALI 2 44 mm
AL8035 (2..4) IP67 DALI 2 48 mm

Drivers 500mA

on/off
AL1074 (1..2) IP20 30 mm
AL1077 (1..2) IP20 40 mm
AL1084 (1..3) IP20 S.P. 55 mm
AL9051 (1..3) IP67 44 mm

dimmable
AL4010 (1..4) IP20 PUSH 0/1..10V 72 mm
ALMINI50 (1..2) IP20 DALI 2 PUSH 30 mm
AL4151 (1..4) IP20 DALI 2 PUSH 72 mm
AL4153 (1..4) IP20 PUSH IGBT-TRIAC 56 mm
AL6050 (1..2) IP67 DALI 2 44 mm
AL8050 (2..4) IP67 DALI 2 48 mm