FLEXA
LIGHTING

MINE 10

Adjustable downlight

design Lapo Grassellini

70mm IP20 made in Italy



The Mine range of adjustable recessed luminaires combines outstanding performance with incredibly compact dimensions. The recessed optic ensures a high level of visual comfort. Featuring an innovative design developed to optimise heat dissipation, the range offers the possibility to combine different colour temperatures and beam angles.

La gamma di incassi orientabili Mine combina altissime prestazioni ad una dimensione incredibilmente contenuta. L'ottica arretrata garantice un alto comfort visivo. Rivoluzionari per il design funzionale alla dissipazione, offrono la possibilità di combinare temperature colore ed aperture di fascio.

La gamme d'encastrés orientables Mine associe des performances exceptionnelles à des dimensions incroyablement compactes. L'optique en retrait garantit un haut niveau de confort visuel. Dotée d'un design innovant conçu pour optimiser la dissipation thermique, la gamme permet de combiner différentes températures de couleur et différents angles de faisceau.

Die schwenkbaren Einbauleuchten der Serie Mine verbinden außergewöhnlich hohe Leistung mit äußerst kompakten Abmessungen. Die zurückversetzte Optik gewährleistet einen hohen visuellen Komfort. Ihr innovatives, auf eine optimale Wärmeableitung ausgelegtes Design ermöglicht die Kombination verschiedener Farbtemperaturen und Abstrahlwinkel.

La gama de luminarias empotrables orientables Mine combina prestaciones excepcionalmente elevadas con dimensiones increíblemente compactas. La óptica retranqueada garantiza un elevado confort visual. Caracterizada por un diseño innovador desarrollado para optimizar la disipación térmica, la gama permite combinar diferentes temperaturas de color y aperturas de haz.


Supply current
250mA (V_f 36V)

Power
10W


CRI
85 (2200K)
93 (2700K-3000K-4000K)

2-Step MacAdam

Dimensions



Photometric diagrams



CCT/CRI/Flux

2200K	**810 lm**
2700K	**840 lm**
3000K	**930 lm**
4000K	**960 lm**

Code construction

MN1 X X X

S	**M**	**W**	
36°	46°	60°	
18	**29**	**39**	**49**
2200K	2700K	3000K	4000K
1	**2**	**5**	**6**
White	Grey	Black	Bronze

Accessories

SMN101
Milky screen

Note
The screen must be ordered together with the lighting fixture.

Drivers 250mA

on/off
AL1025 (1) IP20 40 mm

dimmable
AL4030 (1) IP20 0/1..10V 55 mm
ALMINI25 (1) IP20 DALI 2 PUSH 30 mm
AL4031 (1) IP20 DALI 2 55 mm
AL4032 (1) IP20 IGBT-TRIAC 55 mm