FLEXA
LIGHTING

TASK 10

Recessed optic downlight

60mm **IP44 made in Italy**

design Roberto Mantovani



A compact recessed luminaire with a recessed optic, designed to produce an extremely narrow 10° beam. Its clean, perfectly controlled light distribution allows for precise and effective applications, enhancing architectural details and display elements.

Apparecchio da incasso ad ottica arretrata, dalle dimensioni compatte, progettato per generare un fascio luminoso estremamente stretto di 10°. L'emissione pulita e perfettamente controllata consente applicazioni precise ed efficaci, valorizzando dettagli architettonici ed elementi espositivi.

Un luminaire encastré compact à optique en retrait, conçu pour générer un faisceau lumineux extrêmement étroit de 10°. Son émission nette et parfaitement maîtrisée permet des applications précises et efficaces, mettant en valeur les détails architecturaux et les éléments exposés.

Eine kompakte Einbauleuchte mit zurückversetzter Optik, die für einen extrem engen Abstrahlwinkel von 10° entwickelt wurde. Die saubere und präzise kontrollierte Lichtverteilung ermöglicht gezielte und wirkungsvolle Anwendungen zur Hervorhebung architektonischer Details und von Ausstellungsobjekten.

Una luminaria empotrable compacta con óptica retranqueada, diseñada para generar un haz luminoso extremadamente estrecho de 10°. Su emisión limpia y perfectamente controlada permite aplicaciones precisas y eficaces, realzando detalles arquitectónicos y elementos expositivos.

Supply current

250mA (V_f 36V)

Power


10W

CRI


85 (2200K) - 93 (2700K-3000K-4000K)

2-Step MacAdam

Dimensions



Photometric diagrams



CCT/CRI/Flux

2200K	**810 lm**
2700K	**840 lm**
3000K	**930 lm**
4000K	**960 lm**

Code construction

TW X XX 1

Beam angle 10°

18	29	39	49
2200K	2700K	3000K	4000K

1	2	5	6
White	Grey	Black	Bronze

Drivers 250mA

on/off

AL1025 (1) IP20 40 mm

dimmable

AL4030 (1) IP20 0/1..10V 55 mm
ALMINI25 (1) IP20 DALI 2 PUSH 30 mm
AL4031 (1) IP20 DALI 2 55 mm
AL4032 (1) IP20 IGBT-TRIAC 55 mm