FLEXA
LIGHTING

TUBE 6

Ceiling mounted luminaire

AC CC

AC IP40 CC IP44 made in Italy

design Lapo Grassellini



The Tube 6 range of ceiling luminaires combines minimal geometry with a high level of mechanical and optical quality. The rearward optical system ensures elevated visual comfort. Equipped with COB Fidelity, it is designed for a CRI98 and R9 93.

La gamma di apparecchi a plafone Tube 6 combina una geometria minimale ad una qualità meccanica ed ottica di alto livello. L'ottica arretrata garantisce un alto comfort visivo. Equipaggiati con COB Fidelity si connota per un CRI98 e R9 93.

La gamme d'appareils pour plafonds Tube 6 associe géométrie minimale et qualité mécanique et optique de haut niveau. L'optique en retrait garantit un confort visuel élevé. Équipés de COB Fidelity, les appareils se caractérisent par un IRC98 et R9 93.

Die Deckenleuchten-Serie Tube 6 verbindet eine minimale Geometrie mit hoher mechanischer und optischer Qualität. Die Rückenoptik garantiert einen hohen Sehkomfort. Ausgestattet mit COB Fidelity ist sie für einen CRI98 und R9 93 konnotiert.

La gama de luminarias de techo Tube 6 combina una geometría minimalista con una alta calidad mecánica y óptica. La óptica hacia atrás garantiza un alto confort visual. Equipados con COB Fidelity se caracteriza por un CRI98 y R9 93.

Supply current
500mA (V_f 9V) **(CC)**
230VAC **(AC)**


Power
6W

Series wiring (CC)


CRI
85 (2200K)
98 (2700K-3000K-4000K)

2-Step MacAdam

Dimensions



Photometric diagrams



CCT/CRI/Flux

2200K — **490 lm**
2700K — **540 lm**
3000K — **600 lm**
4000K — **620 lm**

Code construction

TB6 X X X X

- 4th X: AC (On board driver) / CC (Remote driver)
- 3rd X: 1 (2200K) / 2 (2700K) / 3 (3000K) / 4 (4000K)
- 2nd X: 1 (35°) / 2 (45°)
- 1st X: 1 (White) / 2 (Grey) / 5 (Black) / 6 (Bronze)

Accessories

LTB601
Low luminance louver

Note
The filter must be ordered together with the lighting fixture.

Drivers 500mA
CC versions only
on/off
AL1074 (1..2) IP20 30 mm
AL1077 (1..2) IP20 40 mm
AL1084 (1..3) IP20 S.P. 55 mm
dimmable
AL4010 (1..4) IP20 PUSH 0/1..10V 72 mm
ALMINI50 (1..2) IP20 DALI 2 PUSH 30 mm
AL4151 (1..4) IP20 DALI 2 PUSH 72 mm
AL4153 (1..4) IP20 PUSH IGBT-TRIAC 56 mm