

DESCRIPTION

Soul Ceiling is defined by two light discs supported by a rod that anchors them to the ceiling. The light passes through the overlapping satin glass and metal diffusers, creating a uniform luminous presence. The central rod, in light or dark burnished brass or matte black, integrates a downward directional light. Soul is also available in the Suspension version.

PRODUCTS DETAILS

FUNCTION	CEILING
LOCATION	INTERIOR
LIGHT EMISSION	DIRECTIONAL AND DIFFUSED LIGHT
LIGHT SOURCE	COB LED 1,7W 168lm 2700°K + STRIP LED 19,2W/m 2700 TOT. = 13,5W 1179lm
ENERGY EFFICIENCY	COB LED = F / STRIP LED = G
RATED VOLTAGE	110 - 120 V / 220 - 240 V
FREQUENCY	50 - 60Hz
SUPPLY	TERMINAL BLOCK
BALLAST	BALLAST INCLUDED

DALI or TRIAC dimming kit available upon request.
Flat Canopy available upon request.

CERTIFICATION

UL WIRED / CE / IP20

MATERIALS

STRUCTURE

M11	LIGHT BURNISHED BRASS
M12	DARK BURNISHED BRASS
MB	MATTE BLACK

GLASS

S	WHITE SATIN

PACKAGE

QTY	**DIMENSIONS**	**NET WEIGHT**	**GROSS WEIGHT**	**TOTAL VOL.**
1 × BOX	48 × 48 × H 46 cm (18”9 × 18”9 × 18”)	10 kg	12 kg	0,10 m^3

DIMENSIONS

